



## 255 MultiMax™



Private Residence, Woodbridge, CT  
Architect: Inter-design Ltd., Old Lyme, CT  
Contractor: Sasso Tile, West Haven, CT



- Superior non-sag performance on large format tile and stone
- Reinforced with Kevlar® for added strength
- Non-slump properties for heaviest tile in medium bed application
- Inhibits the growth of stain-causing mold and mildew in the mortar with Microban® antimicrobial protection
- GREENGUARD certified, low VOC

LATICRETE® 255 MultiMax™ is designed for both light commercial and residential tile and stone applications. Reinforced with Kevlar®, LATICRETE 255 MultiMax provides unmatched, non-sag performance and adjustability on walls. In addition, LATICRETE 255 MultiMax can be used as a medium bed mortar for up

to 3/4" (18 mm) thick applications without any slump or sag. LATICRETE 255 MultiMax has superior bond strength in virtually all ceramic tile and stone installations. This thin-set mortar replaces mastic, thin-bed and medium bed mortars, thereby making LATICRETE 255 MultiMax the ultimate one step multipurpose mortar.

FEATURES	BENEFITS
3 in 1 Multipurpose Mortar	Carry only one product onto the job site for virtually all applications: walls, floors and stone applications; Use as a mastic, multipurpose and medium bed mortar
Non-Sag Performance	Allows for easy installation of small and large format tile and stone without sagging, resulting in fast and easy vertical installations
Medium Bed Mortar	Provides non-slump performance as a medium bed mortar up to 3/4" (18 mm) to install uneven, ungauged and large body stone or tile
Kevlar® Reinforced	Exclusive feature provides added bond strength and unmatched non-sag performance for successful installations of tile and stone every time
Lightweight Mortar	Incredibly lightweight consistency allows for easy troweling onto the substrate with minimal effort; A 40 lb. (18.2 kg) bag of LATICRETE® 255 MultiMax™ provides the same coverage as a 50 lb. (22.7 kg) standard thin-set mortar
A component of the LATICRETE 10 Year Systems Warranty and Lifetime Residential Warranty†	Performance backed by LATICRETE means assurance and peace of mind for trouble-free installations in both interior and exterior applications
Contains Microban®	Inhibits the growth of stain-causing mold and mildew in the mortar with Microban antimicrobial protection
GREENGUARD Certified for Better Indoor Air Quality	Contributes to LEED certification and Low VOCs

## Uses

- For wall installations of interior and exterior ceramic tile and stone
- Can be used as a medium bed mortar for floor installations
- Ideal for showers, bathrooms and wet areas where mastic should be avoided

## Suitable Substrates

- Exterior Glue Plywood\*      ▪ Concrete
- Concrete Block                ▪ Ceramic Tile
- Cement Backer Board\*\*      ▪ Gypsum Wallboard\*
- Masonry and Brick

\*Interior use only

\*\*Consult cement backer board manufacturer for specific installation recommendations and to verify acceptability for exterior use

## Packaging

- 40 lb. (18.2 kg) bag
- 20 lb. (9.1 kg) bag (white only)

## Available Colors

Grey and White

### Approximate Coverage: 40 lb (18.2 kg) bags

**WALL APPLICATIONS – 6.25 QUARTS (5.9 ℓ) OF WATER\***

1/4" x 1/4" (6 mm x 6 mm) notched trowel      72 – 88 ft<sup>2</sup> / 6.5 – 8.2 m<sup>2</sup>

1/4" x 3/8" (6 mm x 9 mm) notched trowel      48 – 58 ft<sup>2</sup> / 4.4 – 5.4 m<sup>2</sup>

**MEDIUM BED APPLICATIONS – 6.25 QUARTS (5.9 ℓ) OF WATER\***

1/2" x 1/2" (12 mm x 12 mm) notched trowel      36 – 44 ft<sup>2</sup> / 3.3 – 4.1 m<sup>2</sup>

**THIN BED APPLICATIONS – 7 QUARTS (6.7 ℓ) OF WATER\***

1/4" x 1/4" (6 mm x 6 mm) notched trowel      80 – 98 ft<sup>2</sup> / 7.4 – 9.1 m<sup>2</sup>

1/4" x 3/8" (6 mm x 9 mm) notched trowel      54 – 66 ft<sup>2</sup> / 5.0 – 6.1 m<sup>2</sup>

\*See Data Sheet 255.0 for more information

LATICRETE INTERNATIONAL, INC.

One LATICRETE Park North  
Bethany, CT 06524-3423 USA  
800.243.4788  
203.393.0010  
www.laticrete.com

† See Data Sheets 700.12 and 230.12 for complete warranty information.